


## TE 106 breaker and scaler

### Applications

- Light chiselling and corrective work on concrete and masonry
- Removing rough edges and projections
- Concrete repair work
- Removing tiles and plaster
- Exposing rebars
- Removing paint and rust from steel (using the needle adaptor)
- Cleaning construction equipment (using the needle adaptor)

Technical data	TE 106
Rated power input:	700 W
Single impact energy:	2.4 joules
Hammering speed:	0–4,080 blows per min.
Dimension (L × W × H):	360 × 90 × 210 mm
Weight in accordance with EPTA – Procedure 01/2003:	3.6 kg
Protection class II (double insulated)	
The product complies with the following directives and standards: 89/336/EEC, 98/37/EC, EN 60745-1, EN 60745-2-6, EN 55014-1, EN 55014-2, EN 61000-3-2, EN 61000-3-3.	



### TE 106 breaker and scaler

Ordering designation	Item no.
<b>TE 106 breaker and scaler (110V) tool only</b>	<b>228680</b>

Complete with 4-metre supply cord, impact-resistant plastic toolbox, Hilti tool grease, cleaning cloth, operating instructions, safety instructions.

Ordering designation	Item no.
<b>TE 106 breaker and needle adaptor kit (110V)</b>	<b>3430800</b>

Complete with 4-metre supply cord, impact-resistant plastic toolbox, Hilti tool grease, cleaning cloth, operating instructions, safety instructions and needle adaptor.

### Advantages

- Secure hold and easy to guide thanks to ergonomic rubber-padded front grip
- Quick-change chuck for rapid switching between chisels and needle adaptor
- Maintenance-free thanks to permanent lubrication



### Accessories

Ordering designation	Item no.
<b>TE 106 needle adaptor</b>	<b>271959</b>
<b>TE 104 needle adaptor</b>	<b>232800</b>
<b>Needles (single replacement needles)</b>	<b>223428</b>
<b>Needle set (19 needles)</b>	<b>232860</b>

